



# GARLAND INDUSTRIES

## Material Safety Data Sheet (MSDS)

Revised 2/11

THE GARLAND COMPANY, INC.  
3800 EAST 91ST. STREET  
CLEVELAND, OHIO 44105-2197  
PH: (216) 641-7500  
FAX: (216) 641-0633

GARLAND CANADA, INC.  
1296 MARTIN GROVE ROAD  
TORONTO, ONTARIO, M9W 4X3  
PH: (416)747-7995  
FAX: (416)747-1980

Garland Company UK Ltd.  
Unit 5, Glevum Works, Upton Street  
Gloucester, UK GL14LA  
Ph: 01452 330 646  
Fax: 01452 330 657 (only in UK)  
Ph: 011 44 1452 330 646  
Fax: 011 44 1452 330 657 (outside UK)

VOC Compliant

Contact Adhesive

CHEMICAL FAMILY: Aromatic Polyurethane

**Product Name: Dura Walk PS Top Coat Part A**

**Product Code: 2518-10**

TRANSPORTATION EMERGENCY ASSISTANCE / CALL CHEMTREC / 1-800-762-8225

HMIS HAZARD RATINGS

H:2 F:3 R:0 PP: I

DEGREE OF HAZARD: 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT

---

### SECTION II - HAZARDOUS SUBSTANCES

---

	% BY WT	OSHA PEL	ACGIH TLV
Xylene <sup>(1)</sup> ; CAS# 1330-20-7	5.6	100ppm	100ppm
Methyl isobutyl ketone <sup>(1)</sup> ; CAS# 108-10-1	5.7	50ppm	50ppm
Methyl ethyl ketone <sup>(1)</sup> ; CAS # 78-93-3	1.3	200ppm	200ppm

(1) These chemicals are subject to SARA Title III, Section 313 reporting

---

### SECTION III - PHYSICAL DATA

---

**BOILING RANGE:** 237-288° F  
**VAPOR DENSITY**(air=1): Heavier  
**% VOLATILE BY VOLUME:** 28.5 +/- 0.5 %  
**EVAPORATION RATE** (ether=1): Slower  
**VOC:** 210 g/l (A & B Combined)

**WEIGHT PER GALLON:** 14.5 +/- 0.5 Lbs  
**VAPOR PRESSURE** (mm Hg @ 20C)  
Xylene: 6.0  
Methyl isobutyl ketone: 16.5  
Methyl ethyl ketone: 70

---

### SECTION IV - FIRE & EXPLOSION HAZARD DATA

---

**FLASH POINT:** 23° F (TCC)

**EXTINGUISHING MEDIA:** Foam, CO<sub>2</sub>, dry chemical or water fog.

**SPECIAL FIRE FIGHTING PROCEDURES:** Cool containers with water fog to prevent rupture. Boil over may occur when temperature of material approaches boiling point of solvent. Do not extinguish flame at leak because possibility of uncontrolled explosive reignition exists. Cut off fuel and/or allow fire to burn out. Extinguish residual fires with chemical powder or foam.

**UNUSUAL FIRE & EXPLOSION HAZARD:** Spills or vapor leaks readily form flammable mixtures at or above the flash point. It is unlikely that this product will explode due to mechanical impact but fire or explosion may occur from static accumulation and discharge.

=====  
**SECTION V - HEALTH HAZARD DATA**  
=====

**EFFECTS OF OVEREXPOSURE:** Inhalation of high concentrations can produce central nervous system depression. Skin contact can cause severe irritation, possible burns, defatting and dermatitis. Eye contact causes severe irritation, redness, tearing and blurred vision.

**EMERGENCY & FIRST AID:** If overcome by vapors, remove to fresh air and if breathing has stopped, give artificial respiration.

**EYE CONTACT:** Flush immediately with water and call a physician as soon as possible.

**SKIN CONTACT:** Wash with soap and water and remove contaminated clothing.

**INGESTION:** See a physician as soon as possible.

**PRIMARY ROUTES OF ENTRY:** Dermal or inhalation most likely.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:** Repeated exposure can cause allergic reaction with development of occupational asthma. Long term exposure to low vapor concentrations may cause chronically progressive pulmonary disease. Repeated skin contact can result in sensitization.

=====  
**SECTION VI - REACTIVITY DATA**  
=====

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Heat, sparks and open flame

**INCOMPATIBILITY:** Avoid strong oxidizing materials like liquid chlorine and concentrated oxygen.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Incomplete burning may produce carbon monoxide and/or carbon dioxide.

**HAZARDOUS POLYMERIZATION:** Will not occur.

=====  
**SECTION VII - SPILL OR LEAK PROCEDURES**  
=====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all

sources of ignition. Keep people away. Avoid breathing vapors.

Recover

free liquid and add absorbent to remainder of spill before collecting with non-sparking tools.

**WASTE DISPOSAL METHOD:** Dispose in accordance with local, state, and federal regulations.

=====  
**SECTION VIII - SPECIAL PROTECTION INFORMATION**  
 =====

**RESPIRATORY PROTECTION:** Contains isocyanates when mixed with Dura Walk PS Part B. Air purifying respirators with organic vapor cartridges are appropriate when the material is trowel, roller or squeegee applied. A self-contained or supplied air breathing apparatus may be required if material is heated and spray applied in poorly ventilated areas.

**VENTILATION (Local/Mechanical Exhaust):** Explosion proof mechanical equipment capable of keeping vapor concentration below the PEL.

**PROTECTIVE GLOVES:** Chemical resistant gloves. Nitrile recommended

**EYE PROTECTION:** Safety goggles or face shield.

**OTHER PROTECTIVE EQUIPMENT:** Eye bath & safety shower should be available.

=====  
**SECTION IX - SPECIAL PRECAUTIONS & TOXICOLOGICAL PROPERTIES**  
 =====

**SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING & STORING:** Keep containers closed and store in a cool dry place with adequate explosion proof ventilation. Keep away from heat, sparks and open flame. Ground equipment to prevent accumulation of static charge.

**TOXICOLOGICAL PROPERTIES:** Available data shows that none of the ingredients are carcinogenic, teratogenic or mutagenic but solvents contained may be harmful or fatal if swallowed. Vapor harmful. May cause skin or eye irritation.

=====  
**SECTION X - TRANSPORT INFORMATION**  
 =====

**SHIPPING NAME:** PAINT, 3, UN1263, PGII  
 PAINT, 3, UN1263, PGII, LTD.QTY.

**GROUND:** For standard ground shipping see required labels and markings. Package in 1A2 metal pails. An outer box is not required

**Exceptions:**

**(173.150) Limited Quantities: (Labels & Placards not required)**

Inner packaging's not over .3 gal each packed in a strong outer packaging, max package weight 66 lbs.

**(173.173) Paint, paint related materials, adhesives, inks and resins:**

Authorized combination packaging: Metal receptacle in a 4G box.

Authorized single packaging: 1A1 or 1A2 pail or drum

**AIR (CARGO ONLY):** Max 15.8 gal in a 1A1 tight head pail or  
 Max 2.64 gal per can in a 4G box max 15.8 gal per package  
 Packaging Instructions - 307

**AIR (PASSENGER & CARGO):** Max 1.3 gal per package  
Max 1.3 gal per can in a 4G box  
No single packaging allowed  
Packaging Instructions - 305  
**Ltd.Qty. (Labels required)**  
Max 16.9 oz per container  
Max 33.8 oz per package  
Max 66 lbs per package  
Packaging Instructions Y305

**AIR (UPS):** Same as passenger

**OCEAN:** Max 181 lbs per package  
Max 10.5 gal per metal container or 7.9 gal per plastic container in  
a 4G box or a 1H1 or 1H2 plastic pail or a 1A1 or 1A2 metal pail.

**MISC:** ERG# 128  
NMFC: 149980.2

**REQUIRED LABELS & MARKINGS (AIR, OCEAN AND STANDARD GROUND)**

**Preparation Date** 24-Feb-2009  
**Revision Date** 21-Feb-2011  
**Revision Summary** Hazard warnings updated

**Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.



## GARLAND INDUSTRIES

### Material Safety Data Sheet (MSDS)

Revised 2/11

THE GARLAND COMPANY, INC.  
3800 EAST 91ST. STREET  
CLEVELAND, OHIO 44105-2197  
PH: (216) 641-7500  
FAX: (216) 641-0633

GARLAND CANADA, INC.  
1296 MARTIN GROVE ROAD  
TORONTO, ONTARIO, M9W 4X3  
PH: (416)747-7995  
FAX: (416)747-1980

Garland Company UK Ltd.  
Unit 5, Glevum Works, Upton Street  
Gloucester, UK GL14LA  
Ph: 01452 330 646  
Fax: 01452 330 657 (only in UK)  
Ph: 011 44 1452 330 646  
Fax: 011 44 1452 330 657 (outside UK)

VOC Compliant

Contact Adhesive

CHEMICAL FAMILY: Aromatic Polyurethane

**Product Name: Dura Walk PS Top Coat Part B****Product Code: 2518-10**

TRANSPORTATION EMERGENCY ASSISTANCE / CALL CHEMTREC / 1-800-762-8225

HMIS HAZARD RATINGS

H:2 F:3 R:1 PP:1

DEGREE OF HAZARD: 4=EXTREME 3=HIGH 2=MODERATE 1=SLIGHT 0=INSIGNIFICANT

#### SECTION II - HAZARDOUS SUBSTANCES

	% BY WT	OSHA PEL	ACGIH TLV
Toluene diisocyanate <sup>(1) (2)</sup>	<0.1	0.02ppm	0.005ppm
Xylene <sup>(1)</sup> ; CAS# 1330-20-7	9.8	100ppm	100ppm
Methyl isobutyl ketone <sup>(1)</sup> ; CAS# 108-10-1	10.4	50ppm	50ppm

(1) These chemicals are subject to SARA Title III, Section 313 reporting

(2) These chemicals are subject to SARA Title III, Section 313 reporting

#### SECTION III - PHYSICAL DATA

**BOILING RANGE:** 237-243° F**VAPOR DENSITY**(air=1): Heavier**% VOLATILE BY VOLUME:** 22.2%**EVAPORATION RATE**(ether=1): Slower**VOC:** 210 g/l (A & B Combined)**WEIGHT PER GALLON:** 8.8 +/- 0.25 Lbs**VAPOR PRESSURE** (mm Hg @ 20C)

Xylene: 6.0

Methyl isobutyl ketone: 16.5

Toluene diisocyanate: &lt;0.01

#### SECTION IV - FIRE & EXPLOSION HAZARD DATA

**FLASH POINT:** 60° F (TCC)

**EXTINGUISHING MEDIA:** Foam, CO<sub>2</sub>, dry chemical or water fog.

**SPECIAL FIRE FIGHTING PROCEDURES:** Firefighters must wear self-contained breathing apparatus and full protective clothing. Cool containers with water fog. Do not spray pool fires directly; a solid stream of water directed into hot burning liquid can cause frothing. Boil over may occur when temperature of material approaches boiling point of solvent.

**UNUSUAL FIRE & EXPLOSION HAZARD:** Spills or vapor leaks readily form flammable mixtures at or above the flash point. Contamination of this product with water will generate carbon dioxide gas with possible build-up of pressure in confined spaces. It is unlikely that this product will explode due to mechanical impact but fire or explosion may occur from static accumulation and discharge.

=====  
**SECTION V - HEALTH HAZARD DATA**  
=====

**EFFECTS OF OVEREXPOSURE:** Inhalation of high concentrations can produce central nervous system depression. Skin contact can cause severe irritation, possible burns, defatting and dermatitis. Eye contact causes severe irritation, redness, tearing and blurred vision.

**EMERGENCY & FIRST AID:** If overcome by vapors, remove to fresh air and if breathing has stopped, give artificial respiration.

**Eye contact:** Flush immediately with water and call a physician as soon as possible.

**Skin contact:** Wash with soap and water and remove contaminated clothing.

**Ingestion:** See a physician as soon as possible.

**PRIMARY ROUTES OF ENTRY:** Dermal or inhalation most likely.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:** Repeated exposure can cause allergic reaction with development of occupational asthma. Long term exposure to low vapor concentrations may cause chronically progressive pulmonary disease. Repeated skin contact can result in sensitization.

=====  
**SECTION VI - REACTIVITY DATA**  
=====

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Heat, sparks, flame and water contamination

**INCOMPATIBILITY:** Water, alcohols, liquid chlorine, concentrated oxygen, NaOH, amines, alkaline materials and organometallic compounds.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Burning may produce nitrogen oxides, hydrogen cyanide, carbon monoxide and/or carbon dioxide.

**HAZARDOUS POLYMERIZATION:** reacts slowly with water to produce CO<sub>2</sub> gas

=====  
**SECTION VII - SPILL OR LEAK PROCEDURES**  
=====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus. Cover spills with sawdust, vermiculite, or other absorbent material. Add an equal volume of a 6% ammonia solution in water and allow to react for 10 minutes. Collect

into open containers and add more solution, Cover loosely to vent carbon dioxide gas generated.

**WASTE DISPOSAL METHOD:** Dispose in accordance with local, state, and federal regulations.

=====  
**SECTION VIII - SPECIAL PROTECTION INFORMATION**  
 =====

**RESPIRATORY PROTECTION:** Air purifying respirators with organic vapor cartridges are appropriate when the material is trowel, roller or squeegee applied. A self-contained or supplied air breathing apparatus may be required if material is heated and spray applied in poorly ventilated areas.

**VENTILATION (Local/Mechanical Exhaust):** Explosion proof mechanical equipment capable of keeping vapor concentration below the PEL.

**PROTECTIVE GLOVES:** Chemical resistant gloves. Nitrile recommended

**EYE PROTECTION:** Safety goggles or face shield.

**OTHER PROTECTIVE EQUIPMENT:** Eye bath & safety shower should be available.

=====  
**SECTION IX - SPECIAL PRECAUTIONS & TOXICOLOGICAL PROPERTIES**  
 =====

**SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING & STORING:** Keep containers closed. Store in a cool dry place with adequate explosion proof ventilation. Open containers should be blanketed with dry nitrogen before resealing if there is no moisture contamination. If water contamination is suspected, do not reseal. Ground equipment to prevent accumulation of static charge.

**TOXICOLOGICAL PROPERTIES:** This product may contain trace amounts of Toluene diisocyanate monomer (TDI). The National Toxicological Program reported that when toluene diisocyanate was introduced into a rat's stomach there was an increase in tumors over non-exposed rats.

=====  
**SECTION X - TRANSPORT INFORMATION**  
 =====

**SHIPPING NAME:** PAINT, 3, UN1263, PGII  
 PAINT, 3, UN1263, PGII, LTD.QTY.

**GROUND:** For standard ground shipping see required labels and markings. Package in 1A2 metal pails. An outer box is not required

**Exceptions:**

**(173.150) Limited Quantities: (Labels & Placards not required)**

Inner packaging's not over .3 gal each packed in a strong outer packaging, max package weight 66 lbs.

**(173.173) Paint, paint related materials, adhesives, inks and resins:**

Authorized combination packaging: Metal receptacle in a 4G box.

Authorized single packaging: 1A1 or 1A2 pail or drum

**AIR (CARGO ONLY):** Max 15.8 gal in a 1A1 tight head pail or  
 Max 2.64 gal per can in a 4G box max 15.8 gal per package  
 Packaging Instructions - 307

**AIR ( PASSENGER & CARGO):** Max 1.3 gal per package  
Max 1.3 gal per can in a 4G box  
No single packaging allowed  
Packaging Instructions - 305  
**Ltd.Qty.: (Labels required)**  
Max 16.9 oz per container  
Max 33.8 oz per package  
Max 66 lbs per package  
Packaging Instructions Y305

**AIR (UPS):** Same as passenger

**OCEAN:** Max 181 lbs per package  
Max 10.5 gal per metal container or 7.9 gal per plastic container in  
a 4G box or a 1H1 or 1H2 plastic pail or a 1A1 or 1A2 metal pail.

**MISC:** ERG# 128  
NMFC: 149980.2

**REQUIRED LABELS & MARKINGS (AIR, OCEAN AND STANDARD GROUND)**

**Preparation Date** 24-Feb-2009  
**Revision Date** 21-Feb-2011  
**Revision Summary** Hazard warnings updated

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.