



# Rust-Go® VOC Top Coat White

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

## SECTION 1: IDENTIFICATION

### Product Identifier

**Product Form:** Mixture

**Product Name:** Rust-Go VOC Top Coat White

**Product Code:** 1522

### Intended Use of the Product

Quick-drying, environmentally-friendly rust inhibitive primer. For professional use only.

### Name, Address, and Telephone of the Responsible Party

#### **Manufacturer**

The Garland Company, Inc.  
3800 East 91<sup>st</sup> Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633  
www.garlandco.com

#### **Supplier**

The Garland Company, Inc.  
3800 East 91<sup>st</sup> Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633  
www.garlandco.com

Garland Canada, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8  
T-416-747-7995  
F-416-747-1980  
www.garlandco.com

### Emergency Telephone Number

**Emergency Number:** 1-800-262-8200 (CHEMTREC)

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the Substance or Mixture

#### **Classification (GHS-US)**

Flam. Gas 1	H220
Flam. Liq. 1	H224
Carc. 2	H225
Flam. Liq. 4	H227
Press. Gas Liquefied gas	H280
Acute Tox. 4	H302
Asp.Tox. 1	H304
Acute Tox. 1	H315
Skin Irrit. 2	H317
Eye Dam. 1	H318
Flam. Liq. 2	H319
Skin Sens. 1	H330
Eye Irrit. 2A	H331
Carc. 2	H332
Carc. 1B	H335
Germ Cell Muta. 1	H340
STOT SE 3	H350
STOT SE 3	H351
STOT RE 1	H372
STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Acute 2	H401
Aquatic Acute 3	H402
Aquatic Chronic 1	H410
Aquatic Chronic 3	H412

### Label Elements

#### **GHS-US Labeling**

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

### Hazard Pictograms (GHS-US)

:



GHS02



GHS07



GHS08



GHS09

### Signal Word (GHS-US)

: Danger

### Hazard Statements (GHS-US)

: H220-Extremely flammable gas  
H224-Extremely flammable liquid and vapor  
H225-Highly flammable liquid and vapor  
H227-Combustible liquid  
H280-Contains gas under pressure; may explode if heated  
H302-Harmful if swallowed  
H304-May be fatal if swallowed and enters airways  
H315-Causes skin irritation  
H317-May cause an allergic skin reaction  
H318-Causes serious eye damage  
H319-Causes serious eye irritation  
H330-Fatal if inhaled  
H331-Toxic if inhaled  
H332-Harmful if inhaled  
H335-May cause respiratory irritation  
H340-May cause genetic defects by route of exposure if conclusively proven that no other route applies  
H350-May cause cancer by route of exposure if conclusively proven that no other route applies  
H351-Suspected of causing cancer by route of exposure if conclusively proven that no other route applies.  
H372-Causes damage to organs through prolonged or repeated exposure by route of exposure if conclusively proven that no other route applies  
H373-May cause damage to organs through prolonged or repeated exposure by route of exposure if conclusively proven that no other route  
H400-Very toxic to aquatic life  
H401-Toxic to aquatic life  
H402-harmful to aquatic life  
H410-Very toxic to aquatic life with long lasting effects  
H412-harmful to aquatic life with long lasting effects

### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting/ equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe gas.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash face, hands and any exposed skin thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P281 - Use personal protective equipment as required.

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
 P284 - Wear respiratory protection.  
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 - IF exposed or concerned: Get medical advice/attention.  
 P310 - Immediately call a POISON CENTER or doctor/physician.  
 P311 - Call a POISON CENTER or doctor/physician.  
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.  
 P314 - Get medical advice/attention if you feel unwell.  
 P320 - Specific treatment is urgent (see supplemental first aid instructions on this label).  
 P321 - Specific treatment (see supplemental first aid instructions on this label).  
 P330 - Rinse mouth.  
 P331 - Do NOT induce vomiting.  
 P332 + P313 - If skin irritation occurs: Get medical advice/attention.  
 P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P337 + P313 - If eye irritation persists: Get medical advice/attention.  
 P362 - Take off contaminated clothing and wash before reuse.  
 P363 - Wash contaminated clothing before reuse.  
 P370 + P378 - In case of fire: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
 P381 - Eliminate all ignition sources if safe to do so.  
 P391 - Collect spillage.  
 P403 - Store in a well-ventilated place.  
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 - Store in a well-ventilated place. Keep cool.  
 P405 - Store locked up.  
 P410 + P403 - Protect from sunlight. Store in a well-ventilated place.  
 P501 - Dispose of contents/container to an approved landfill.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Component

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Benzyl chloride	(CAS No) 100-44-7		Flam. Liq. 4, H227 Acute Tox. 4, H302 Acute Tox. 1, H315 Skin Irrit. 2, H317 Eye Dam. 1, H318 Skin Sens. 1, H330 Carc. 1B, H335 STOT SE 3, H350 STOT RE 2, H373
1,4-Dioxane	(CAS No) 123-91-1		Flam. Liq. 2, H319

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

			Eye Irrit. 2A, H335 Carc. 2, H225 STOT SE 3, H351
Quartz	(CAS No) 14808-60-7	5-10	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Zinc Oxide	(CAS No) 1314-13-2	5-10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Acetaldehyde	(CAS No) 75-07-0		Flam. Liq. 1, H224 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 3, H402
Ethylene oxide	(CAS No) 75-21-8		Flam. Gas 1, H220 Press. Gas Liquefied gas, H280 Acute Tox. 3, H315 Skin Irrit. 2, H319 Eye Irrit. 2A, H331 Muta.1B, H335 Carc. 1B, H340 STOT SE 3, H350 Aquatic Chronic 3, H412
Ethyl benzene	(CAS No) 100-41-4		Flam. Liq. 2, H225 Acute Tox. 4, H351 Carc. 2, H332 STOT RE 2, H373 Asp.Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** May cause irritation of respiratory tract.

**Skin Contact:** Substance may cause slight skin irritation.

**Eye Contact:** May cause slight irritation.

**Ingestion:** Ingestion can cause irritation to mucous membranes.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** No further relevant information available.

### Indication of Immediate Medical Attention and Special Treatment Needed

**General:** No further relevant information available.

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media:** Not available.

### Special Hazards Arising From the Substance or Mixture

**Hazardous Combustion Products:** Not available.

**Fire and Explosion Hazards:** None.

### Advice for Firefighters

**Fire Fighting Procedures:** Exercise caution when fighting any chemical fire.

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

**Protection During Firefighting:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Use personal protective equipment.

#### Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Keep out of waterways.

#### Methods and Materials for Containment and Cleaning Up

**For Containment and Cleaning Up:** Dike with inert absorbent material. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

### SECTION 7: HANDLING AND STORAGE

#### Precautions for Safe Handling

**General Handling:** Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment.

Avoid contact with skin and eyes.

#### Conditions for Safe Storage

**General:** Keep container tightly closed in a dry and well-ventilated place. Keep at temperatures above 0°C.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	ACGIH TLV	OSHA PEL	Ontario TWAEV	Mexico
Ethyl benzene	TWA: 100 ppm STEL: 125 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	STEL: 540 mg/m <sup>3</sup> STEL: 125 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm STEL: 545 mg/m <sup>3</sup> TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
Benzyl chloride	TWA: 1 ppm	TWA: 1 ppm TWA: 5 mg/m <sup>3</sup>	TWA: 1 ppm TWA: 5 mg/m <sup>3</sup>	TWA: 1 ppm TWA: 5 mg/m <sup>3</sup>
1,4-Dioxane	TWA: 20 ppm Skin	TWA: 100 ppm TWA: 360 mg/m <sup>3</sup> Skin	TWA: 20 ppm Skin	STEL: 100 ppm STEL: 360 mg/m <sup>3</sup> TWA: 90 mg/m <sup>3</sup> TWA: 25 ppm
Zinc Oxide	TWA: 2 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>
Acetaldehyde	Ceiling: 25 ppm	TWA: 360 mg/m <sup>3</sup> TWA: 200 ppm	CEV: 25 ppm	Ceiling: 45 mg/m <sup>3</sup> Ceiling: 25 ppm
Ethylene oxide	TWA: 1 ppm	TWA: 1 ppm	STEL: 18 mg/m <sup>3</sup> STEL: 10 ppm TWA: 1.8 mg/m <sup>3</sup> TWA: 1 ppm	TWA: 1 ppm TWA: 2 mg/m <sup>3</sup>
Quartz (Crystalline Silica)	TWA: 0.025 mg/m <sup>3</sup>		TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>

Chemical Name	NIOSH IDLH
Ethyl benzene	800 ppm
Benzyl chloride	10 ppm
1,4-Dioxane	500 ppm
Zinc Oxide	500 mg/m <sup>3</sup>
Acetaldehyde	2000 ppm
Ethylene oxide	800 ppm
Quartz (Crystalline Silica)	50 mg/m <sup>3</sup>

#### Control Parameters

**Appropriate Engineering Controls:** Do not allow ventilation equipment to draw material odors indoors.

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

### Personal Protective Equipment

**Eye/face Protection :** Tightly fitting safety goggles.

**Skin Protection:** Long sleeved clothing. Protective gloves.

**Respiratory Protection :** No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

**Hand Protection:** Wear impervious gloves such as vinyl to minimize contact with skin.



**Environmental Exposure Controls:** No specific controls are needed.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Color	: Gray
Odor	: Slight
Odor Threshold	: Not applicable
pH	: 9.5
Melting Point	: No test data available
Freezing Point	: 32°F / 0°C
Boiling Point (760 mm Hg)	: 212-212°F / 100100°C
Density	: 10.945 (lbs/gal)
Flash Point – Closed Cup	: Not available
Evaporation Rate (Butyl Acetate =	: Slower than butyl acetate
Flammability (solid, gas)	: Not applicable
Flammability Limits in Air	: Lower: No test data available; Upper: No test data available
Vapor Pressure	: Not determined.
Vapor Density (Air = 1)	: Not available
Specific Gravity (H <sub>2</sub> O = 1)	: 1.3116
Solubility in Water (by wt)	: Partial
Explosion Limits	: Not available
Volatiles	: Not available
VOC	: <50 g/L

## SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Not available.

**Chemical Stability:** Stable under normal conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization does not occur under normal conditions.

**Conditions to Avoid:** Temperatures above 0°C.

**Incompatible Materials:** No materials to be especially mentioned.

**Hazardous Decomposition Products:** None under normal use.

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

#### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl benzene	3500 mg/kg Rat	15354 mg/kg Rabbit	17.2 mg/L Rat 4 h
Benzyl chloride	340 mg/kg Rat		0.74 mg/L Rat 4 h
1,4-Dioxane	7120 mg/kg Rat	7600 µL/kg Rabbit	
Zinc Oxide	5000 mg/kg Rat		

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

Acetaldehyde	661 mg/kg Rat	3540 mg/kg Rabbit	13300 mg/kg Rat 4 h
Ethylene oxide	0.05 mg/kg Rat		1.44 mg/L Rat 4 h 800 ppm Rat 4 h 9 mg/L Rat 1 h
Quartz (Crystalline Silica)	500 mg/kg Rat		

## Chronic Toxicity

**California Proposition 65:** WARNING: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

Chemical Name	ACGIH	IARC	NTP	OSHA	Mexico
Ethyl benzene	A3	Groupe 2B		X	
Benzyl chloride	A3	Group 2A		X	A3
1,4-Dioxane	A3	Group 2B	Reasonably Anticipated	X	
Acetaldehyde	A3	Group 2B	Reasonably Anticipated	X	A3
Ethylene oxide	A2	Group 1	Known	X	A2
Quartz (Crystalline Silica)	A2	Group 1	Known	X	

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### Ethyl benzene

#### Freshwater Algae Data

*Selenastrum capricornutum* EC50=4.6 mg/L (72 h)

*Selenastrum capricornutum* EC50>438 mg/L (96 h)

#### Microtox Data

*Photobacterium phosphoreum* EC50=9.68 mg/L (30 min)

*Nitrosomonas* EC50=96 mg/L (24 h)

#### Water Flea Data

*Daphnia magna* EC50 1.8 - 2.4 mg/L (48 h)

### Benzyl chloride

#### Microtox Data

*Photobacterium phosphoreum* EC50=1.92 mg/L (5 min)

*Photobacterium phosphoreum* EC50=2.25 mg/L (15 min)

*Photobacterium phosphoreum* EC50=2.97 mg/L (30 min)

### 1,4-Dioxane

#### Microtox Data

*Photobacterium phosphoreum* EC50=610 mg/L (5 min)

*Photobacterium phosphoreum* EC50=668 mg/L (15 min)

*Photobacterium phosphoreum* EC50=733 mg/L (30 min)

#### Water Flea Data

water flea EC50=163 mg/L (48 h)

### Acetaldehyde

#### Freshwater Algae Data

*Nitzschia linearis* EC50 237 - 249 mg/L (120 h)

#### Microtox Data

*Photobacterium phosphoreum* EC50=280.6 mg/L (15 min)

*Photobacterium phosphoreum* EC50=280.6 mg/L (25 min)

*Photobacterium phosphoreum* EC50=280.6 mg/L (5 min)

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 10/12/2015

### Water Flea Data

*Daphnia magna* EC50=48.3 mg/L (48 h)

water flea EC50=9000 mg/L (48 h)

Water Flea Data

*Daphnia magna* EC501.8 - 2.4 mg/L (48 h)

### Ethylene oxide

#### Water Flea Data

*Daphnia magna* EC50=137 mg/L (48 h)

### Persistence/Degradability:

Not available

### Bioaccumulation/ Accumulation:

Not available

### Mobility in Environmental Media:

Not available

### Benzyl chloride

log Pow = 2.3

### 1,4-Dioxane

log Pow = -0.42

### Acetaldehyde

log Pow = 0.5

### Ethylene oxide

log Pow = -0.3

### Ethyl benzene

log Pow = 3.118

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of in accordance with local, state, and federal regulations.

**Unused and Contaminated Product:** Empty containers should be taken for local recycling, recovery or waste disposal.

Chemical Name	RCRA
Benzyl chloride - 100-44-7	waste number P028
1,4-Dioxane - 123-91-1	waste number U108
Ethylene oxide - 75-21-8	waste number U115

## SECTION 14: TRANSPORT INFORMATION

### 14.1 In Accordance with DOT

Proper Shipping Name : Not regulated

Hazard Class :

Identification Number :

Packing Group :

### 14.2 In Accordance with IMDG

Proper Shipping Name

Hazard Class



# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

**Identification Number** : Not regulated

**Packing Group** :

:

:

### 14.3 In Accordance with IATA

**Proper Shipping Name** : Not regulated

**Hazard Class** :

**Identification Number** :

**Packing Group** :

### 14.4 In Accordance with Mexico

**Proper Shipping Name** : Not regulated

**Hazard Class** :

**Identification Number** :

**Packing Group** :

## SECTION 15: REGULATORY INFORMATION

### International Inventories

All of the components in the product are on the following Inventory lists:

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	CHINA	KECL	PICCS	AICS
Ethyl benzene	X	X	-	X	-	X	X	X	X	X
Benzyl chloride	X	X	-	X	-	X	X	X	X	X
1,4-Dioxane	X	X	-	X	-	X	X	X	X	X
Zinc Oxide	X	X	-	X	-	X	X	X	X	X
Acetaldehyde	X	X	-	X	-	X	X	X	X	X
Ethylene oxide	X	X	-	X	-	X	X	X	X	X
Quartz (Crystalline Silica)	X	X	-	X	-	X	X	X	X	X

<b>TSCA</b>	Complies
<b>DSL</b>	Complies
<b>NDSL</b>	Complies
<b>EINECS</b>	Complies
<b>ELINCS</b>	Does not Comply
<b>ENCS</b>	Complies
<b>CHINA</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

### USA

#### Federal Regulations:

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values
Ethyl benzene (CAS #: 100-41-4)	0.1%
Benzyl chloride (CAS #: 100-44-7)	1.0%
1,4-Dioxane (CAS #: 123-91-1)	0.1%

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 10/12/2015

Acetaldehyde (CAS #: 75-07-0)	0.1%
Ethylene oxide (CAS #: 75-21-8)	0.1%

### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs.

#### Chemical Name

Ethyl benzene (CAS #: 100-41-4)

Benzyl chloride (CAS #: 100-44-7)

1,4-Dioxane (CAS #: 123-91-1)

Acetaldehyde (CAS #: 75-07-0)

Ethylene oxide (CAS #: 75-21-8)

#### State Regulations:

##### California Proposition 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.


Chemical Name	CAS-No	Category	Type
Ethyl benzene	100-41-4	Carcinogen	
Benzyl chloride	100-44-7	Carcinogen	
1,4-Dioxane	123-91-1	Carcinogen	
Acetaldehyde	75-07-0	Carcinogen	
Ethylene oxide	75-21-8	Carcinogen	Female Reproductive
Quartz (Crystalline Silica)	14808-60-7	Carcinogen	

#### State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl benzene	X	X	X	X	X
Benzyl chloride	X	X	X	X	X
1,4-Dioxane	X	X	X	X	X
Zinc Oxide	X	X	X		X
Acetaldehyde	X	X	X	X	X
Ethylene oxide	X	X	X	X	X
Quartz (Crystalline Silica)	X	X	X		X

#### Canada:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Rust-Go® VOC Top Coat White	
WHMIS Classification	D2A Very toxic materials 

Chemical Name	NPRI
Ethyl benzene	X
Benzyl chloride	X
1,4-Dioxane	X
Acetaldehyde	X
Ethylene oxide	X

# Rust-Go VOC Top Coat White

## Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

### SECTION 16: OTHER INFORMATION

<b>Revision Date</b>	:	October 12, 2015
<b>Other Information</b>	:	This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.
<b>Party Responsible for the Preparation of This Document</b>	:	The Garland Company, Inc. 3800 East 91 <sup>st</sup> Street Cleveland, Ohio 44105-2197 T-1800-762-8225 F-216-641-0633

*This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.*