



# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Revision Date: 05/13/2015 Date of issue: 06/01/2015

Version: 1.0

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Form:** Mixture

**Product Name:** Weatherking®

**Product Code:** 7336

#### Intended Use of the Product

Cold process, asphalt modified, interply adhesive. For professional use only.

#### Name, Address, and Telephone of the Responsible Party

##### Manufacturer

The Garland Company, Inc.  
3800 East 91<sup>st</sup> Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633  
www.garlandco.com

##### Supplier

The Garland Company, Inc.  
3800 East 91<sup>st</sup> Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633

The Garland Company, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8  
T-416-747-7995 800-387-5991  
F-416-747-1980

#### Emergency Telephone Number

**Emergency number** : 1-800-762-8225 24 hours

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### Classification (GHS-US)

Flam. Liq. 3 H226  
Eye Irrit. 2A H319  
Muta. 1B H340  
Carc. 1A H350  
STOT RE 2 H373  
Asp. Tox. 1 H304  
Aquatic Acute 1 H400  
Aquatic Chronic 2 H411

#### Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H319 - Causes serious eye irritation  
H340 - May cause genetic defects  
H350 - May cause cancer (Inhalation)  
H373 - May cause damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

##### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, open flames, sparks. - No smoking  
P233 - Keep container tightly closed

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe mist/vapors/spray  
P264 - Wash hands, forearms, and exposed areas thoroughly after handling  
P273 - Avoid release to the environment  
P280 - Wear eye protection, protective gloves, protective clothing  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P314 - Get medical advice and attention if you feel unwell  
P331 - If swallowed, do NOT induce vomiting  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P370+P378 - In case of fire: Use appropriate media to extinguish  
P391 - Collect spillage  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container according to local, regional, national, and international regulations

### Other Hazards

**Other Hazards Not Contributing to the Classification:** Contains a small amount of hydrogen sulfide. Hydrogen sulfide is a fatal and highly flammable gas with a rotten egg odor that quickly causes odor fatigue. Heating of this product and storage under elevated temperatures or over long periods of time may release higher amounts of hydrogen sulfide. Hydrogen sulfide is also an asphyxiant.

### Unknown Acute Toxicity (GHS-US)

<2% of the mixture consists of ingredients of unknown acute toxicity.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Asphalt	(CAS No) 8052-42-4	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Carc. 2, H351
Stoddard solvent	(CAS No) 8052-41-3	10 - 30	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Hydrogen sulfide	(CAS No) 7783-06-4	1 - 5	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 Eye Irrit. 2A, H319 STOT SE 1, H370 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 - 4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

			Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Attapulгите	(CAS No) 12174-11-7	1 - 4	Carc. 2, H351
Cumene	(CAS No) 98-82-8	1 - 2	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 STOT SE 1, H370 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	1 - 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	1 - 2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
1,3,5-Trimethylbenzene	(CAS No) 108-67-8	1 - 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Cellulose	(CAS No) 9004-34-6	0.5 - 1.5	Comb. Dust
Quartz	(CAS No) 14808-60-7	0.1 - 1	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Alcohols, C9-11-iso-, C10-rich	(CAS No) 68526-85-2	0.01	Aquatic Acute 1, H400

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If exposed or concerned: Get medical advice/attention.

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. If exposed or concerned: Get medical advice/attention.

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

**Skin Contact:** Remove contaminated clothing. Rinse affected area with water for at least 5 minutes.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### **Most Important Symptoms and Effects Both Acute and Delayed**

**General:** May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation.

**Inhalation:** May cause cancer by inhalation.

**Skin Contact:** Causes skin irritation.

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** May cause genetic defects. May cause cancer.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If medical advice is needed, have product container or label at hand.

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use water jet. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Not available

**Firefighting Instructions:** Exercise caution when fighting any chemical fire.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur and/or nitrogen. Hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures. Corrosive vapors.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Handle in accordance with good industrial hygiene and safety practice. Do not allow product to spread into the environment.

#### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Evacuate unnecessary personnel.

#### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Collect spillage. Clear up spills immediately and dispose of waste safely.

### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

### SECTION 7: HANDLING AND STORAGE

#### Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable. Contains Sulfur, may release small amounts of hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

#### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Specific End Use(s)** Adhesive

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control Parameters

Asphalt (8052-42-4)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup>
Hydrogen sulfide (7783-06-4)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	14 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	21 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (ppm)	10 ppm
USA IDLH	US IDLH (ppm)	100 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	125 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Stoddard solvent (8052-41-3)		
Mexico	OEL TWA (mg/m <sup>3</sup> )	523 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	1050 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	200 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2900 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	20000 mg/m <sup>3</sup>

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

Ontario	OEL TWA (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup> (140°C Flash aliphatic solvent)
<b>1,3,5-Trimethylbenzene (108-67-8)</b>		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	125 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	655 mg/m <sup>3</sup>
Mexico	OEL STEL (ppm)	150 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OEL TWA (ppm)	100 ppm
<b>Quartz (14808-60-7)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	250 mppcf/%SiO <sub>2</sub> +5, 10mg/m <sup>3</sup> /%SiO <sub>2</sub> +2
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	0.10 mg/m <sup>3</sup> (designated substances regulation)
<b>Kaolin (1332-58-7)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica)
<b>Attapulgite (12174-11-7)</b>		
Québec	VEMP (mg/m <sup>3</sup> )	1 fibers/cm <sup>3</sup>
<b>Cellulose (9004-34-6)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Limestone (1317-65-3)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
<b>Cumene (98-82-8)</b>		
Mexico	OEL TWA (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
Mexico	OEL TWA (ppm)	50 ppm
Mexico	OEL STEL (mg/m <sup>3</sup> )	365 mg/m <sup>3</sup>

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	245 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	900 ppm (10% LEL)
Ontario	OEL TWA (ppm)	50 ppm

### Magnesium carbonate (546-93-0)

Mexico	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Mexico	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica)

### Exposure Controls

**Appropriate Engineering Controls:** Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Take precautionary measures against static discharges. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapours may be released.

**Personal Protective Equipment:** On heating: wear respiratory equipment. Protective clothing. Protective goggles. Gloves.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses.

**Skin and Body Protection:** Not available

**Respiratory Protection:** When manufacturing or handling product in large quantities and vapors or mists may be generated, maintain airborne concentrations below recommended limits. Workplace risk assessments should be completed before specifying and implementing respirator usage. NIOSH approved respirators for protection should be used if respirators are found to be necessary.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Viscous, Black
Odor	: Petroleum distillate
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 149 - 199 °C (300.2-390.2°F)
Flash Point	: 41 °C (105.8°F) TCC
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

<b>Lower Flammable Limit</b>	: Not available
<b>Upper Flammable Limit</b>	: Not available
<b>Vapor Pressure</b>	: Not available
<b>Relative Vapor Density at 20 °C</b>	: Not available
<b>Relative Density</b>	: Not available
<b>Specific Gravity</b>	: 0.9
<b>Solubility</b>	: Insoluble
<b>Partition coefficient: n-octanol/water</b>	: Not available
<b>Viscosity</b>	: Not available
<b>Explosion Data – Sensitivity to Mechanical Impact</b>	: Not expected to present an explosion hazard due to mechanical impact.
<b>Explosion Data – Sensitivity to Static Discharge</b>	: Not expected to present an explosion hazard due to static discharge.
<b>VOC</b>	: 300 g/L

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). May release flammable gases. Contains a small amount of hydrogen sulfide. Hydrogen sulfide is a fatal, and highly flammable gas with a rotten egg odor that quickly causes odor fatigue. Heating of this product and storage under elevated temperatures or over long periods of time may release higher amounts of hydrogen sulfide. Hydrogen sulfide is also an asphyxiant.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** May cause genetic defects.

**\_\_\_Teratogenicity:** Not available

**Carcinogenicity:** May cause cancer (Inhalation).

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause cancer by inhalation.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** May cause genetic defects. May cause cancer.

#### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Asphalt (8052-42-4)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
<b>Hydrogen sulfide (7783-06-4)</b>	
LC50 Inhalation Rat (mg/l)	0.99 mg/l (Exposure time: 1 h)



# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat (mg/l)	18 g/m <sup>3</sup> (Exposure time: 4 h)
<b>Stoddard solvent (8052-41-3)</b>	
LD50 Oral Rat	> 5 g/kg Behavioral somnolence
LD50 Dermal Rabbit	> 3 mg/kg
<b>1,3,5-Trimethylbenzene (108-67-8)</b>	
LC50 Inhalation Rat (mg/l)	24 g/m <sup>3</sup> (Exposure time: 4 h)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 Oral Rat	4300 mg/kg
LC50 Inhalation Rat (mg/l)	47635 mg/l/4h (Exposure time: 4 h)
LC50 Inhalation Rat (ppm)	6247 ppm/4h (species: Sprague-Dawley)
<b>Quartz (14808-60-7)</b>	
LD50 Oral Rat	> 5000 mg/kg
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (ppm)	3400 ppm/4h
<b>Cellulose (9004-34-6)</b>	
LC50 Inhalation Rat (mg/l)	> 5800 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Alcohols, C9-11-iso-, C10-rich (68526-85-2)</b>	
LD50 Oral Rat	> 2648 mg/kg
LD50 Dermal Rabbit	> 3.16 mg/kg
LC50 Inhalation Rat (ppm)	> 95.3 ppm
<b>Aluminum hydroxide (Al(OH)3) (21645-51-2)</b>	
LD50 Oral Rat	> 5000 mg/kg
<b>Cumene (98-82-8)</b>	
LD50 Oral Rat	2260 mg/kg
LD50 Dermal Rabbit	10000 mg/kg
LC50 Inhalation Rat (mg/l)	20 - 40 mg/l (Exposure time: 6 h)
<b>Asphalt (8052-42-4)</b>	
IARC Group	2B
National Toxicity Program (NTP) Status	Twelfth Report - Items under consideration.
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC Group	3
<b>Quartz (14808-60-7)</b>	
IARC Group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.
<b>Attapulgit (12174-11-7)</b>	
IARC Group	2B, 3
<b>Styrene-butadiene copolymer (9003-55-8)</b>	
IARC Group	3
<b>Cumene (98-82-8)</b>	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

### SECTION 12: ECOLOGICAL INFORMATION

#### Toxicity

**Ecology - General:** Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

<b>Hydrogen sulfide (7783-06-4)</b>	
LC50 Fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC 50 Fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
LC50 Fish 1	7.19 (7.19 - 8.28) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Stoddard solvent (8052-41-3)</b>	
LC50 Fish 1	0.42 mg/l
<b>1,3,5-Trimethylbenzene (108-67-8)</b>	
LC50 Fish 1	3.48 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 Fish 1	3.3 mg/l
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC 50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
LC50 Fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Alcohols, C9-11-iso-, C10-rich (68526-85-2)</b>	
LC50 Fish 1	3 mg/l
LC50 other aquatic organisms 1	2.4 mg/l Algae
EC50 Daphnia 1	4 µg/l
<b>Cumene (98-82-8)</b>	
LC50 Fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Persistence and Degradability</b>	
<b>Weatherking®</b>	
Persistence and Degradability	Not established. May cause long-term adverse effects in the environment.
<b>Bioaccumulative Potential</b>	
<b>Weatherking®</b>	
Bioaccumulative Potential	Not established.
<b>Asphalt (8052-42-4)</b>	
BCF fish 1	(no bioaccumulation expected)
Log Pow	> 6
<b>Hydrogen sulfide (7783-06-4)</b>	
BCF fish 1	(no bioaccumulation expected)
Log Pow	0.45 (at 25 °C)
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Log Pow	3.63
<b>Stoddard solvent (8052-41-3)</b>	
Log Pow	3.16 (Octanol/water partition coefficient 3.16/7.06)

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 (0.6 - 15)
Log Pow	2.77 - 3.15

  

<b>Cumene (98-82-8)</b>	
BCF fish 1	35.5
Log Pow	3.55 (at 23 °C)

**Mobility in Soil** Not available

### **Other Adverse Effects**

**Other Information:** Avoid release to the environment.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Hazardous waste due to toxicity. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## **SECTION 14: TRANSPORT INFORMATION**

### **14.1 In Accordance with DOT**

**Proper Shipping Name** : Not regulated  
**Hazard Class** :  
**Identification Number** : UN1999  
**Label Codes** :  
**Packing Group** :  
**ERG Number** :

### **14.2 In Accordance with IMDG**

**Proper Shipping Name** : TARS, LIQUID  
**Hazard Class** : 3  
**Identification Number** : UN1999  
**Packing Group** : III  
**Label Codes** : 3  
**EmS-No. (Fire)** : F-E  
**EmS-No. (Spillage)** : S-E  
**MFAG Number** : 130



### **14.3 In Accordance with IATA**

**Proper Shipping Name** : TARS, LIQUID  
**Packing Group** : III  
**Identification Number** : UN1999  
**Hazard Class** : 3  
**Label Codes** : 3  
**ERG Code (IATA)** : 3L



### **14.4 In Accordance with TDG**

**Proper Shipping Name** : Not regulated  
**Packing Group** :  
**Hazard Class** :  
**Identification Number** :  
**Label Codes** :

## **SECTION 15: REGULATORY INFORMATION**

### **US Federal Regulations**

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

<b>Asphalt (8052-42-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Hydrogen sulfide (7783-06-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 302 (Specific toxic chemical listings)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
<b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>	500
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Benzene, 1,2,4-trimethyl- (95-63-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Stoddard solvent (8052-41-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>1,3,5-Trimethylbenzene (108-67-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>1-Propanamine, 3-(isodecyloxy)-, acetate (28701-67-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
<b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>	100 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Quartz (14808-60-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Kaolin (1332-58-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Styrene-butadiene copolymer (9003-55-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cellulose (9004-34-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Alcohols, C9-11-iso-, C10-rich (68526-85-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Aluminum hydroxide (Al(OH)3) (21645-51-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Limestone (1317-65-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cumene (98-82-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>SARA Section 313 - Emission Reporting</b>	1.0 %

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

### **Magnesium carbonate (546-93-0)**

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### **US State Regulations**

#### **Quartz (14808-60-7)**

##### **U.S. - California - Proposition 65 - Carcinogens List**

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### **Attapulгите (12174-11-7)**

##### **U.S. - California - Proposition 65 - Carcinogens List**

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### **Cumene (98-82-8)**

##### **U.S. - California - Proposition 65 - Carcinogens List**

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### **Asphalt (8052-42-4)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **Hydrogen sulfide (7783-06-4)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **Benzene, 1,2,4-trimethyl- (95-63-6)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **Stoddard solvent (8052-41-3)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **1,3,5-Trimethylbenzene (108-67-8)**

RTK - U.S. - Massachusetts - Right To Know List

#### **Xylenes (o-, m-, p- isomers) (1330-20-7)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **Quartz (14808-60-7)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **Kaolin (1332-58-7)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

#### **Cellulose (9004-34-6)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### Limestone (1317-65-3)

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### Cumene (98-82-8)

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### Magnesium carbonate (546-93-0)

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

### Canadian Regulations

#### Weatherking®

WHMIS Classification

Class B Division 3 - Combustible Liquid

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects



### Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

### Hydrogen sulfide (7783-06-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification

Class A - Compressed Gas

Class B Division 1 - Flammable Gas

Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### Benzene, 1,2,4-trimethyl- (95-63-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification

Class B Division 3 - Combustible Liquid

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification

Class B Division 3 - Combustible Liquid

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### 1,3,5-Trimethylbenzene (108-67-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification

Class B Division 3 - Combustible Liquid

### 1-Propanamine, 3-(isodecyloxy)-, acetate (28701-67-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Quartz (14808-60-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Kaolin (1332-58-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Styrene-butadiene copolymer (9003-55-8)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
<b>Cellulose (9004-34-6)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
<b>Alcohols, C9-11-iso-, C10-rich (68526-85-2)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Aluminum hydroxide (Al(OH)3) (21645-51-2)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
<b>Limestone (1317-65-3)</b>	
Listed on Non-Domestic Substances List (NDSL)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Cumene (98-82-8)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Magnesium carbonate (546-93-0)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision date** : 05/13/2015

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**Party Responsible for the Preparation of This Document**

# Weatherking®

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 05/13/2015 Date of Issue: 06/01/2015

---

The Garland Company, Inc.  
3800 East 91st Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225

*This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.*

North America GHS US 2015 & WHMIS